

激光测距仪

Laser Distance Meter

SW-TAL

项目 ITEMS	参数
测量范围 Measurement Range	50m/70m/100m
测量精度 Accuracy	±(2mm+D*1/10000)
显示屏幕 Screen	2.2吋黑白屏
角度测量范围 Dip Measuring Range	±90°
角度精度 Angle Accuracy	±1°
激光类型 Laser Type	Class II 630-670nm, <1mW
连续测量 Continuous Measurement	√
面积/体积测量 Area/ Volume Measurement	√
墙面面积测量 Wall area Measurement	√
勾股测量 Pythagorean Measurement	√
测角测高功能 Angle And Height Measurement	√
加减测量功能 Add/Subtract Measurement	√
面积体积加减 Area&Volume Addition Subtraction	√
最大/最小测量 Max/Min Value	√
语音播报 Voice Prompt	√
自助校准 Self-Calibration	√
底座螺纹尺寸	1/4寸铜螺母
自动关闭激光 Auto Laser-off	20s(单次测/Single Measurement)
自动关机 Auto Power-off	150s
存储记录笔数 Max Storage	100笔/Units
电池类型 Battery	3.7V 600mAh 锂电池 Li-ion
USB充电时长 USB Charging Time	约1.5小时/About 1.5 hours
测距电池工作时间 Measurement Times At Full Charge	≥5500次(仅激光测距, 语音开) /Single measuring 5500 times
存储温湿度 Storage Temperature&Humidity	-20°C~60°C, 10%~90%RH
工作温度 Working Temperature&Humidity	0°C~40°C, 10%~90%RH
机身尺寸 Product Dimension	118x54x26.5mm



■ 投线参数

投线激光类型 Line Projection Laser Type	Class II 630-670nm; <1mW
报警角度	±4°(投线激光闪烁)
投线工作距 Working Distance of Line Projection	5m清晰可见(环境光<300LUX)
线功率 Linear Power Rating	< 1mW@10cm
线宽 Line Width	≤3mm (5m处)
自动关机 Auto-off	30分 (可选) /30min (optional)
投线电池工作时间	约5小时 (连续)

■ 机械卷尺参数

卷尺量程 Measuring Range	2m
卷尺最小刻度 The Minimum Scale	1mm
卷尺单位 Unit	单面公英制 Single-sided imperial system
尺带宽度 Tape Width	9.0mm
尺带厚度 Tape Thickness	0.1mm
尺带材质 Tape Material	65锰钢 (黄底黑字) Manganese Steel
尺带精度 Tape Accuracy	±1mm
卷尺自锁功能 Self-Locking	X

深达威科技(广东)股份有限公司

Sndway Technology (Guangdong) co., Ltd.
地址: 东莞市虎门镇虎门团结路58号深达威科技园
Add: Sndway Science & Technology Industrial Park, 58
Tuanjie Road, Humen 523930, Dongguan, China
邮箱/E-mail: market@sndway.com
全国咨询服务热线/Service Hotline: 400-125-6969
网址/Url: www.sndway.com 电话/Tel: 0769-85265688



官网/WEB



关注公众号