

双向激光测距仪

Dual Laser Distance Meter

SW-210RT/211RT

项目 ITEMS	SW-210RT	SW-211RT
测量范围 Measurement Range	60m(单向/Unidirectional) 120m(双向/Bidirectional)	100m(单向/Unidirectional) 200m(双向/Bidirectional)
测量精度 Accuracy	± (2mm+D*1/10000) (单向/Unidirectional)	
显示屏 Screen	2.0英寸彩屏 / 2.0" Color LCD	
蓝牙通讯功能 Bluetooth	可选/Chinese Market Only	
倾角测量范围 Dip measuring range	±90°	
连续测量 Continuous Measurement	√	
面积/体积测量 Area/Volume Measurement	√	
墙面面积测量 Wall area measurement	√	
勾股测量 Pythagorean Measurement	√	
测角测高功能 Angle and Height Measurement	√	
加减测量功能 Addition/Subtraction Measurement	√	
最大/最小测量 Max/Min Value	√	
电子水平泡 Electronic level bubble	√	
自动转屏 Automatic screen rotation	√	
磁吸 Magnetism	√	
存储笔数 Max Storage	100	
激光等级 Laser Level	Class II	
激光类型 Laser Type	630-670nm <1mW	
自动关闭激光 Auto Laser-off	20s (单次测量/Single Measurement)	
自动关机 Auto Power-off	180s	
背光时间 Backlight time	60s	
电池类型 Battery	3.7V 850mAh锂电池 Li-ion	
充电规格 Charging specification	DC5V 0.75A Type-C	
最大电池寿命 Battery Life	8000次(单向)/8000 Time(Unidirectional) 5000次(双向)/5000 Times(Bidirectional)	
存储温度 Storage Temperature	-20°C~60°C	
工作温度 Working Temperature	0°C~40°C	
存储湿度 Storage Humidity	20%~80%RH	
外形尺寸 Product Dimension	118x54x25.5mm	
外箱尺寸 Carton MEAS	512*300*328mm	
装箱数量 QTY per Carton	40PCS	
重量 G.W per Carton	13.6KG	



深达威科技(广东)股份有限公司

Sndway Technology (Guangdong) co., Ltd.
地址: 东莞市虎门镇虎门团结路58号深达威科技园
Add: Sndway Science & Technology Industrial Park, 58
Tuanjie Road, Humen 523930, Dongguan, China
邮箱/E-mail: market@sndway.com
全国咨询热线/Service Hotline: 400-125-6969
网址/Url: www.sndway.com 电话/Tel: 0769-85265688



官网/WEB



关注公众号